

# Bandsaw type BS G

Best  
Price



BS 280G



BS 315GH

**Bandsaws type BS-280 G** are high-quality machines for professional use. Cast-iron construction and base with built-in coolant system. Quick-adjusting vice, side-gauge and automatic stop. 2-speed motor for optimum cutting speed. Quick-lock system and scale for arm swivelling.

Type **BS-280 G** is equipped with automatic saw frame feed by gravity with hydraulic damper adjustment of down feed speed.

**BS-315 GH** is a sturdy semi-automatic bandsaw for the professional user. The bandsaw is constructed with hydraulically controlled cylinder for both vice and saw frame. 2-speed motor for optimum sawing in all kinds of material. Electro-mechanical belt tensioning. Mitre cutting to both sides. Electrical cooling pump.

| Data                |     | BS 280G         | BS 315GH        |
|---------------------|-----|-----------------|-----------------|
| Article no.         |     | 17914           | 17915           |
| Capacity round 90°  | mm  | 220             | 230             |
| Capacity square 90° | mm  | 250 x 155       | 315 x 170       |
| Capacity round 60°  | mm  | -               | 130 (R)         |
| Capacity square 60° | mm  | -               | 130 x 105 (R)   |
| Capacity round 45°  | mm  | 160             | 210 (R/L)       |
| Capacity square 45° | mm  | 160 x 110       | 210 x 170 (R/L) |
| Capacity round 45°  | mm  | 100             | -               |
| Capacity square 45° | mm  | 80 x 95         | -               |
| Speed range         | RPM | 40 – 80         | 40 - 80         |
| Belt dimensions     | mm  | 2450 x 27 x 0,9 | 2825 x 27 x 0,9 |
| Motor, 1x230 V      | kW  | 0,6 – 0,8       | 0,75 - 1,1      |
| Weight              | kg  | 254             | 380             |