

Lathe type GH 1440B

Best
Price



Type GH 1440B precision lathe with hardened and ground bedways and gears. With Camlock spindle nose for quick change of chucks, foot brake and halogen work lamp. Jog button switch for easy spindle speed selection. Gap bed allows larger diameter work. Gear runs in oil bath. Practical central location of controls.

Standard with digital read-out and quick-change tool post!

Standard equipment:

- Digital read-out, 2-axis
- 200mm / D5 3-Jaw chuck
- Independent 4-Jaw chuck
- Quick change tool post
- Foot brake
- Coolant system
- Work light
- D1-5 Camlock system
- Face plate 250mm
- Steady and follow rest
- Splash guard
- Hardened and ground "V" beds
- Chuck guard
- Morse taper drill sleeve

Data		GH 1440B
Art. No.		17822
Distance btw. centers	mm	1000
Width of bed	mm	187
Center height	mm	178
Swing over cross slide	mm	224
Swing over gap	mm	476
Swing over bed	mm	356
Spindle bore	mm	Ø 51
Tailstock taper		MT 4
Longitudinal feed	mm	0,078 – 1,044
Cross feed	mm	0,022 – 0,298
Speed range	rpm	70 – 2000
Metric thread	mm	0,45 -10,0
Inch thread	TPI	2,25 - 40
Motor	kW	1,5 / 2,2
Dimensions L x W x H	mm	1940 x 760 x 1520
Weight	kg	600