

Milling machine type VM 320C

**Best
Price**



VM 320C

Standard equipment:

- All 3 axes with automatic feed
- Head swivels + / - 45°
- Central lubrication
- Coolant system
- 3-axis digital read-out
- Grounded gears in oil-bath
- Dynamic balancing
- Safety interlock for manual / aut. feed
- Spindle brake
- Halogen work light
- Service tools
- Dovetail guideways on all axes
- Hardened and ground guideways

Heavy Duty gearbox

Head swivel + / - 45°

3-axis digital read out

X, Y and Z-axis with automatic feed

**Spindle speed, 12 step
58-1710 RPM**

| Data | | VM 320C |
|-------------------------|--------|--|
| Art. No. | | 17727 |
| Table dimensions | mm | 1320 x 320 |
| Table rotation | mm | 900 (manuel 1000) |
| Table travel X - Y axis | mm | 300 |
| Table travel Z – axis | mm | 400 |
| Table feed | mm/min | X-axis (8) 20-360 Y-axis (8) 20-360 |
| Table rapid feed | mm/min | X-axis 1200 Y-axis 1200 Z-axis 650 |
| T-slots | kW | 4 |
| Motor z-axis | kW | 0,75 |
| Motor feed | kW | 0,55 |
| Spindle taper | | ISO 50 |
| Spindle speed | RPM | 12 / 58-1710 |
| Milling head | | 45° Swivel |
| Spindle to table | mm | 45 – 445 |
| Table load | kg | 300 |
| L X W X H | mm | 2220 x 1810 x 1880 |
| Weight | kg | 2300 |