

Lathe type GH 1340B

**Best
Price**



Type GH-1340B precision lathe with hardened and ground bedways and gears.

With Camlock spindle nose for quick change of chucks, foot brake and halogen work lamp. Jog button switch for easy spindle speed selection. Gap bed allows larger diameter work. Gear runs in oil bath.

Practical central location of controls.

Standard with digital read-out and quick-change tool post!

Standard equipment:

- Digital read-out, 2-axis
- Quick change tool post
- Foot brake
- Coolant system
- Work light
- D1-4 Camlock system
- 3-jaw chuck
- 4-jaw independent chuck
- Face chuck
- Steady and follow rest
- Splatter guard
- Hardened and ground "V" beds
- Chuck guard

Data		GH 1340B
Art. No.		17817
Distance btw. centers	mm	1000
Width of bed	mm	180
Center height	mm	165
Swing over cross slide	mm	180
Swing over gap	mm	470
Swing over bed	mm	330
Spindle bore	mm	38
Tailstock taper		MT 3
Longitudinal feed	mm	(40) 0,053 – 1,291
Cross feed	mm	(40) 0,011 – 0,276
Speed range	RPM	(65) 65 - 1810
Metric thread	mm	(32) 0,4 - 7
Inch thread	TPI	(45) 4 - 60
Motor	kW	1,5
Dimensions L x W x H	mm	1870 x 660 x 1630
Weight	kg	570